

work with a friend





footpath



cycle lanes



weight restriction areas



downtown locations pedestrian zones



factory premises



large-scale retail sites and car parks

GOUPIL G4 • narrow clearance width • very small turning radius • low total weight • 100% electric • 0% local emission Rontex Ecoplow SW01/145 • Quality product • designed and manufactured in Germany

TECHNICAL DATA

GOUPIL G4	
Drive	Electric
Battery	Lead acid/Lithium
Battery power	8,6-21 KWH
Range	up to 199 km WLTP
Top speed	50 km/h
Payload	up to 1.200 KG
Turning radius	3,90 m
Length	3.582 mm
Width without mirrors	1.305 mm
Height	1.893 mm

Rontex Ecoplow SW01/145	
Weight	ca. 77 kg
System overhang	79 cm
Height of blade	145 cm
Quick change device	ca. 55 cm
Lightbar	yes
Weight lightbar	optional

Available spreaders

Lehner Polaro L with additional battery

Rontex GmbH • Ernst-Zindel-Straße 3 • 06847 Dessau-Roßlau















Description	Light construction snow plow with corrosion-resistant material made of laser edged parts with reinforcing ribs and removable fastening system as well as electro-hydraulic control system
Suspension	flexible connection between snow blade and supporting structure via 8 + 1 solid rubber silent blocks
Material carrier	V4A stainless steel (material grade: 1.4571)
Material shield	Polycarbonat / properties 100 % UV-resistant, 87 % translucent, extremely impact-resistant, temperature-resistant, low weight
Scraper bar	Scraper bar fabric-reinforced (5-fold) solid rubber, wear limit: 45 mm
Aggregate	Power unit 3-way hydraulic power unit, closed system incl. expansion tank
Operation blade	via electronic joystick inside the vehicle, 4 directions (blade - up, down, right, left)
Safety	Electrical main switch on the control unit, shut-off valve for hydraulics
Maintenance	100 % maintenance free system
Homologation	Homologation certificate according to § 13 EG-FGV (German homologation)

ADVANTAGES AT A GLANCE / USP

- IMPROVED TRACTION ON THE REAR AXLE
- ✗ NO SHAKING LOOSE OF PAVEMENT STONES
- ✓ CLEANEST CLEARING PATTERN IN ITS CLASS
- SHIELD MATERIAL POLYCARBONATE: UNBREAKABLE, DOES NOT RUST, MAINTENANCE-FREE
- ALL STEEL PARTS V4A: DURABLE, DOES NOT RUST, MAINTENANCE-FREE
- SILENTBLOCK BEARINGS: OPTIMAL ADAPTATION TO THE GROUND, VERY QUIET
- M HYDRAULIC PUMP PROTECTED: NO DAMAGE
 - HIGH PERFORMANCE HYDRAULIC PUMP WITH 4-WAY
- VALVES: SHORT RESPONSE TIME, FAST IN BROACHING MODE

- SCRAPER BAR MADE OF SPECIAL MATERIAL: QUIET, DURABLE, LOW MAINTENANCE
- LOW WEIGHT: APPROX. 77 KG
- OPTIMAL LOAD DISTRIBUTION WHILE MAINTAINING HIGHEST PAYLOAD CAPACITIES
- PERFECT FOR SMALL AND LIGHT COMMERCIAL VEHICLES UP TO APPROX. 3.5 TONS
- ✓ EASY EXCHANGE, DISASSEMBLY
- MULTIPLE USE SUMMER AND WINTER
- C SHORTEST FRONT END IN ITS CLASS = GREATEST POSSIBLE PRESERVATION OF VEHICLE CHARACTERISTICS, E.G. SMALL TURNING CIRCLE

